

TBR SURGICAL PROTOCOL

Connect Implant 8




SURGICAL SEOUENCE

| | 501131125140211131 | | | | | | | | |
|------|--------------------|---|-----------|-----------|--|--|-------------------|--|----------------------|
| | PILOT DRILL | STOP DRILL N°1 | DRILL N°2 | DRILL N°3 | DRILL N°4 | DRILL N°5 | SCREW TAP Ø3,5 | SCREW TAP Ø4 | SCREW TAP Ø5 |
| REF. | A-FPT310 | A-FBXxxx (according to the implant length) | A-FCX200 | A-FCX300 | A-FCX400 | A-FCX500 | A-TAR306 | A-TAR406 | A-TAR506 |
| RPM* | 1200 | 1200 | 1000 | 800 | 600 | 500 | 15 | 15 | 15 |
| Ø3,5 | • | | • | | | | ▶● | | |
| Ø4 | • | 0 | • | • | >0 | | | | |
| Ø5 | • | • | • | • | • | >0 | | | > • |
| | | | 24.00 | | The state of the s | District Control of the Control of t | Manual Box | a de la companya de l | Comment III (Ber 17) |

Trephine the cortical Use the stop drill bone with the pilot drill to facilitate the penetration of the first drill (1200 rpm)*.







For the implants Ø3.5; Ø4 and Ø5: use the drill n°3 to the required length (800 rpm)*.


For the implants Ø4 and Ø5: use the drill n°4 to the required length (600 rpm)*.





Use the screw tap Ø3.5 for the implants Ø3.5 to the required length (15 rpm)*.








O Use of the drill depending on the length of the implant to be placed



For Ø4 implants





SCANORA AND X-RAY TEMPLATE:

Product code: A-TS600

The Connect Implant (diameter and length) is selected using the scanora and X-ray template.

Take into account the tip of the drills which is 1mm long while evaluating the available bone height.



SURGICAL KIT:

Product code: A-TCP006

All the instruments needed to place the Connect Implants are available in the TBR surgical kit.

^{*}The rotation speeds indicated are for information only and depend on the bone quality.



TBR SURGICAL PROTOCOL

Connect Implant 8



CONTRA-ANGLE PROTOCOL

| | | CONTRA-ANGLE SCREWTOOL | MANUAL SCREWTOOL | | |
|------|------------------------------------|------------------------|------------------------------------|--|--|
| REF. | A-MCA325 [long] - A-MCA230 [short] | | A-MCC258 [long] - A-MCC163 [short] | | |
| RPM | N/A | 15 to 20 | Manual | | |



Take the screwtool for contra-angle and clamp the implant inside its packaging. Maintain the contra-angle facing up while moving the implant to the surgical site.



Screw the implant in the alveolar ridge until the implant is completely inserted. NB: Index the implant connection using the visual mark on the screwtool. The laser marking indicates the position of a side of the internal octagon of the implant connection.



well as the contra-angle screwtool.



Remove the contra-angle vertically as If ever the implant is not completely screwed in using the contra-angle, finish the insertion with the torqueratchet wrench [GAN-469-1000203] and its screwtool.



Remove the cover screw from its packaging using the screwtool screwdriver for torqueratchet wrench [GAN-469-1000203]. Maintain the screwtool screwdriver pointing up while transporting the screw to the surgical site. Seal the implant with the cover screw.



Suture the gum. Check radiologically that the implant is perfectly positioned in the bone.

TORQUE-RATCHET WRENCH PROTOCOL

MANUAL SCREWTOOL

| REF. | | A-MCC258 [long] - A-MCC163 [short] |
|------|-----|------------------------------------|
| RPM | N/A | Manual |



Take the screwtool and clamp the implant inside its packaging. Maintain the screwtool pointing up while transporting the implant to the surgical site.



Begin screwing the implant manually.



Finish screwing with the torque-ratchet wrench [GAN-469-1000203]. Screw the implant in the alveolar ridge until the implant is completely inserted. NB: Index the implant connection using the visual mark on the screwtool. The laser marking indicates the position of a side of the internal octagon of the implant connection.



Remove the torque-ratchet wrench [GAN-469-10002031 and pull the screwtool out vertically.



Remove the cover screw from its packaging. Maintain the screwtool screwdriver pointing up while transporting the screw to the surgical site. Seal the implant with the cover screw.



Suture the gum. Check radiologically that the implant is perfectly positioned in the bone.